

YOUR^{POS} TOUCH TERMINAL



YOUR_{POS}

Model		yourPOS FANLESS
Processor		Intel® Atom™ D525, 1M L2 Cache 1.8Ghz
System Memory		2GB, Maximum 4GB (1x204-pin DDR3)
Power Supply		90W (12V / 12.5A) External Power Supply
Storage Device		SSD 120 GB Intel
Graphics		Intel® GMA 3150
Speaker		Internal Speaker 2W x 2
Construction		Aluminum Die-casting + Plastic + Glass
Housing Color		Black with Silver Trim
Touch LCD Display		
Size / Resolution		15" TFT-LCD/ 1024 X 768
Brightness (Backlight Type) & Touch Screen		250 cd/m2 (CCFL); 5-Wire Resistive Touch 350 cd/m2 (LED); 5-Wire Resistive Touch Projected Capacitive Touch (su ordinazione per quantità)
I/O Ports		
Serial Port		3 x External: COM1, COM2 (DB9), COM4 (RJ-45)
USB Port		5 x External (4 Rear + 1 Side)
Cash Drawer Port		1 x RJ11 (12V)
Printer Port		1 x Bi-directional Parallel port
Keyboard / Mouse		1 x PS/2
LAN Port		1 x RJ45 Giga LAN
Audio Port		1 x Line Out
VGA Port 1 x VGA		1 x VGA
DC Output		1 x 12V DC Jack 2.5 mm
Optional I/O Board		
Type A		Serial Port: COM3 & COM5 (RJ-45)
OS Supported		
Windows		POSReady 7 Versione ITA
Physical Dimensions		
Dimensions (WxHxD)		370 (W) x 360 (H) x 235 (D) mm, 7.1 Kg
Environment		
EMI / Safety		CE, FCC Class A
Operating Temperature		0°C ~ 40°C (32°F ~ 104°F)
Optional Peripherals		
Magnetic Stripe Card Reader		Integrated MCR Module (Single / Dual / Triple Track Selectable)
2nd Monitor		Integrated 11.6" or 15" Pole-type LCD Display
Customer Display		Integrated LCM / VFD Customer Display
Wireless LAN		Integrated 802.11 b/g/n Wireless Module
Identification Devices		RFID 13.56 MHz / Fingerprint Reader / i-Button